नेपाल सरकार

कृषि तथा पशुपन्छी विकास मन्त्रालय

इमेल :<u>pmamp.piu.nuwakot@gmail.com</u> वेबसाइट: www.piunuwakot.pmamp.gov.np

फोन नं.: ०१०-५६०२१६,०१०-५६१८४९



परियोजना कार्यान्वयन एकाइ, नुवाकोट

(कार्यक्षेत्रः नुवाकोट र रसुवा जिल्ला)

प.सं.- २०८१/८२ सू.नं.- २३



मितिः२०८१/११/०९

न्युनतम दररेट कायम गरिएको सम्बन्धमा

प्रधानमन्त्री कृषि आधुनिकीकरण परियोजना, परियोजना कार्यान्वयन एकाइ, नुवाकोटको आ.व २०८१/८२ को वार्षिक स्वीकृत कार्यक्रम अनुसार विभिन्न कार्यक्रमहरू सञ्चालनको लागि मिति २०८१/०९/१७ गते प्रकाशित सूचना बमोजिम प्राप्त दररेटहरूको मुल्याङ्कन गर्दा तपशिल बमोजिम स्पेशिफिकेशन अनुसारको कृषि यन्त्र/उपकरणहरूको न्युनतम दररेट निर्धारण गरिएको सम्बन्धित सबैको जानकारीको लागी यो सुचना प्रकाशित गरिएको छ।

तपशिल

having minimum of 24 blades and covering minimum of 700mm tilling width and minimum of 100 mm tilling depth, Gear power transmission with manual shifting of 1- reverse, 2- forward with head light Mini tiller power not less than 4.0±0.2kw, engine model 178F capacity with manual /recoil, Single cylinder,Four stroke, incline/vertical Forced air cooled system,Oil batch type filler, Diesel Engine, Maximum power not less than 4KW at rated speed., A set of rotary rotavator/cultivators attached having minimum of 32 blades and covering minimum of 700mm tilling width and minimum of 100 mm tilling depth,double cluth Gear power transmission with manual shifting of 1-reverse, 2-forward with headlight Power tiller not less than 12HP (8.9kw)Kw capacity, having 4 stroke diesel engine and radiator/hopper water Cooling system, Fuel tank capacity not less than 15 Itr/Minimum ground clearance 185 mm. A set of rotary tiller / cultivators attached having minimum of 24 blades and covering around 900mm tilling width,Gear power transmission with manual shifting, 1-reverse, 3-forward (both high and low) numbers of gears dimenssion: Approx. 750 × 630 × 665 mm; weight: 35-40 kg (approx.); Number of Slats: 11; Transmission System:Pedal crank mechanism; Capacity: 35 kg/hr (approx.) Value Digital Balance Digital display, weighing capacity at least 100 kg, non-corossive material, with user manuals tank capacity of at least 16 ltr, 12v motor powered diaphragm nums of sneed 3300rms, 12v 8AHz rechargeable aluminum processed and covering around specific attacked approxed tank capacity of at least 16 ltr, 12v motor powered diaphragm nums of sneed 3300rms, 12v 8AHz rechargeable aluminum processed and covering around specific attacked processed and covering around specific attacked a	क्र.स.	सामाग्रीको नाम	स्पेसिफिकेशन	एकाइ	न्यूनतम दररेट
	٩	मिनिटिलर	model,capacity with manual/recoilstart, Single cylinder,Four stroke ,incline/vertical Forced air cooled system,Oil batch type filler, Petrol engine, Maximum power not less than 4KW at rated speed, A set of rotary rotavator/cultivators attached having minimum of 24 blades and covering minimum of 700mm tilling width and minimum of 100 mm tilling depth, Gear power transmission with manual shifting of 1- reverse, 2-	संख्या	₹₹ ⊆ 00
Power tiller not less than 12HP (8.9kw)Kw capacity , having 4 stroke diesel engine and radiator/hopper water Cooling system, Fuel tank capacity not less than 15 ltrMinimum ground clearance 185 mm. A set of rotary tiller / cultivators attached having minimum of 24 blades and covering around 900mm tilling width, Gear power transmission with manual shifting, 1-reverse, 3-forward (both high and low) numbers of gears dimenssion :Approx. 750 × 630 × 665 mm; weight :35-40 kg (approx.); Number of Slats:11; Transmission System:Pedal crank mechanism; Capacity :35 kg/hr (approx.) Digital Balance Digital display, weighing capacity at least 100 kg, non-corossive material, with user manuals tank capacity of at least 16 ltr, 12v motor powered diaphragm pump of speed 3300rpm, 12v 8 Abr rechargeable aluminum	R	मिनिटिलर	capacity with manual /recoil, Single cylinder, Four stroke, incline/vertical Forced air cooled system, Oil batch type filler, Diesel Engine, Maximum power not less than 4KW at rated speed., A set of rotary rotavator/cultivators attached having minimum of 32 blades and covering minimum of 700mm tilling width and minimum of 100 mm tilling depth, double cluth Gear power transmission with manual shifting of 1-	संख्या	५००००
४पेडल थ्रेसर(approx.); Number of Slats:11; Transmission System:Pedal crank mechanism; Capacity :35 kg/hr (approx.)संख्या१९६०५Digital BalanceDigital display, weighing capacity at least 100 kg, non-corossive material, with user manualsसंख्या१५००Batterypump of speed 3300rm12v 8A hr rechargeable aluminum	m	पावरटिलर	Power tiller not less than 12HP (8.9kw)Kw capacity, having 4 stroke diesel engine and radiator/hopper water Cooling system, Fuel tank capacity not less than 15 ltrMinimum ground clearance 185 mm. A set of rotary tiller / cultivators attached having minimum of 24 blades and covering around 900mm tilling width,Gear power transmission with manual shifting, 1-reverse, 3-forward (both high and low) numbers of gears	संख्या	१५७०००
tank capacity of at least 16 ltr, 12v motor powered diaphragm	४	पेडल थ्रेसर	(approx.); Number of Slats:11; Transmission System:Pedal	संख्या	११५००
Rattery numn of speed 3300rpm 12v 8 Ahr rechargeable aluminum	પ્ર	Digital Balance	corossive material, with user manuals	संख्या	७८००
इprayer coated of at least 0.4 Mpa working pressure. time of full charge 5 to 8 hrs of gross weight 2.6kg	Ę	Battery sprayer	pump of speed 3300rpm, 12v,8Ahr rechargeable aluminum coated of at least 0.4 Mpa working pressure. time of full charge	संख्या	3700

"आत्मनिर्भर अर्थतन्त्रका लागि कृषिको आधुनिकीकरण, बिशिष्टीकरण र औद्योगिकरण" मित्रलाल कृषिअधिकृत

नेपाल सरकार

कृषि तथा पशुपन्छी विकास मन्त्रालय






प्रधानमन्त्री कृषि आधुनिकीकरण परियोजना

परियोजना कार्यान्वयन एकाइ, नुवाकोट

(कार्यक्षेत्रः नुवाकोट र रसुवा जिल्ला)

प.सं.- २०८१/८२ स्.नं.- २३



7	1 7			^{(४)व} नेवाकोट र रस् ^क
ऋ.स.	सामाग्रीको नाम	स्पेसिफिकेशन	एकाइ	न्यूनतम दररेट रु.
9	Battery sprayer	tank capacity of at least 16 ltr, 12v motor powered diaphragm pump of speed 3300rpm, 12v,8Ahr rechargeable brass coated of at least 0.4 Mpa working pressure. time of full charge 5 to 8 hrs of gross weight 2.6kg	संख्या	३६५०
5	Chaff cutter	Fully automatic conveyor belt feeding having at least 3HP 50HZ/220V, single phase having four number of chopping blade; cutting lenth 15-32mm	संख्या	39000
9	Corn Sheller	Single Tube,Power:at least 0.75 watt,Motor:copper 100%,Capacity:1000-1500kg/hr	संख्या	5000
90	Combined mill	Power Source:at least 3HP, Motor:3HP, voltage and frequency of motor:220volt,50Hz, Rice mill:capacity at least 150kg/hr, Grain grinder: at least 130kg/hr	संख्या	3 2000
99	Pellet Machine	Useage:Domestic,Power Source:Electric Moto,Copper motor,Capacity:at least 60 kg/hr	संख्या	xx000
92	Self propeller reaper	used for harvesting of paddy having not less 4+_0.2kw engine power; fuel tank capacity 3.5 l; cutting width minimum 1000mm and cutting height minimum 40mm having 200kg weight	संख्या	१६५००० .
93	brush cutter	4 stocke petrol engine: not less than 0.9KW, Displacement: Not less than 34 cc, air cooled; weight 7.5kg-10kg; fuel tank capcity not less than 650ml; blade: Baffle type 3 blade with paddy guard.	संख्या	१६५००
98	Disk mill	crush various coarse grains and fodder, such as corn, soyabean, sorghum, dried sweet potato slice and soyabean cake, motor power not less than 7.5KW, motor speed :not less than 1450 rpm, Productivity (kg/hour)not less than 450 kg/hr in case of corn ,Dimension (L x W x H)mm:Around 1050 x 680 x 1325	संख्या	२६०००
94	Petrol Engine Multicrop thresher	Single cylinder, four stock incline/vertical forced air cooled system, oil batch type filter, diesel engine, having maximum power not less than 4 kw; rotor speed not more than 850rpm; rollor length approx. 750mm with actute teeth with approx. 80kg weight	संख्या	४६०००
१६	dipping tank	materail: Fiber Reinforced Plastic (FRP/GRP); dimenssion approx. 110" (Length) x 30" (Width) x 35" (Height); Built-in ladder, waterproof, lightweight, UV-resistant, unbreakable feature and Treating goats, sheep, calves, and other small animals	संख्या	\$ 500

ENTAGED STEAMERSTEINE